

HTH460



TECHNICAL DATA

DIMENSIONS [mm]

| | |
|---------------------------------------|------|
| Width, head open | 1360 |
| Width, head closed | 1200 |
| Height without rotator and link | 1130 |

WEIGHT [kg]

| | |
|--------------------------------------|-----|
| Without rotator and link, from | 890 |
|--------------------------------------|-----|

FELLING/CUTTING

| | |
|---------------------------------------------------------|----------|
| SuperCut 100 saw unit, automatic chain tensioning | Standard |
| Maximum cut diameter [mm] | 620 |
| Length of saw bar [mm] | 640/750 |
| Chain type | .404 |
| Chain speed [m/s] | 40 |

FEEDING, FOUR-WHEEL-DRIVE with steel feed rollers

| | |
|-----------------------------------|------------------|
| Gross feed force [kN] | 400 / 250-cc: 18 |
| | 500 / 315-cc: 22 |
| Maximum feed speed [m/s] | 4.5–7.0 |
| Maximum roller opening [mm] | 560 |

DELIMBING [mm]

| | |
|--------------------------------------|-------------------|
| Delimiting knives | 4 moving, 1 fixed |
| Delimiting diameter tip to tip | 400 |
| Maximum opening upper knives | 560 |
| Maximum opening lower knives | 560 |

HYDRAULIC SYSTEM

| | |
|------------------------------------------|---------|
| Maximum operating pressure [MPa] | 28 |
| Recommended pump capacity [l/min.] | 200–280 |

CONTROL AND MEASURING SYSTEM

For adaptation, contact your local Waratah dealer.

OPTIONAL EQUIPMENT

| | |
|------------------------------------|-----|
| Color marking | Yes |
| Stump treatment | Yes |
| Multi-tree-handling (MTH) | Yes |
| MenSe feed rollers | Yes |
| Moipu feed rollers | Yes |
| Steel thumbnail feed rollers | Yes |
| Steel V-profile feed rollers | Yes |
| Steel ribbed feed rollers | No |
| Chain and saw bar kits | Yes |
| Hydraulic hose kit | Yes |
| Top saw | No |

OTHER ACCESSORIES

For more information, please contact your dealer.